



# JET 210

Jokey Euro Tainer Profi



## basic data

volume to rim: 22,30 l  
weight: 580,0 g  
weight group: Medium


handle type: plastic handle  
handle weight: 25 g

## tolerances

dimensions: +/- 1 mm  
volume/wieght: +/- 5 %

## dimensions

D1: 326,0 mm  
D2: 311,0 mm  
D3: 280,0 mm  
H: 331,0 mm




## Remark

## decoration

height:  
width:  
median breadth:

**IML**  
293,8 mm  
935,8 mm

**Offset**  
240,0 mm  
910,0 mm  
924,0 mm



## lids

### DET 325

weight: 100,0 g  
ISO  
volume: 21,30 l

### dimensions

Ø lid: 325,0 mm  
offset: 250,0 mm  
IML: 279,0 mm

### stacking height

two fold: 652,0 mm  
each  
further: 320,0 mm



### FDET 325

weight: 140,0 g  
ISO  
volume: 22,30 l

### dimensions

Ø lid: 325,0 mm  
offset: 250,0 mm  
IML: 279,0 mm

### stacking height

two fold: 671,0 mm  
each  
further: 329,0 mm



### DET 325R

weight: 120,0 g  
ISO  
volume: 21,10 l

### dimensions

Ø lid: 325,0 mm  
offset: 250,0 mm  
IML: 279,0 mm

### stacking height

two fold: 652,0 mm  
each  
further: 320,0 mm



## logistic information

Max. compression at 20°C on the lowest pallet: 70,00 kg  
layer quantities: 8

### Bucket

pieces per pallet: 320

### DET 325


pieces per pallet: 1920

### FDET 325

pieces per pallet: 720

### DET 325R

pieces per pallet: 960



## material



## QM / certificates



## general information

In our Technical Guidelines you will find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport.

## Misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines "Product" and "Design", which shall also form an integral part of the content of any delivery transaction. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. Technical modifications reserved.