



JET 30

Jokey Euro Tainer Profi



basic data

volume to rim: 3,30 l
weight: 93,0 g
weight group: Medium


handle type: plastic handle
handle weight: 9 g

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

dimensions


D1: 201,5 mm
D2: 184,0 mm
D3: 170,0 mm
H: 138,0 mm



Remark

decoration

	Digital	IML	Offset
height:	85,0 mm	116,4 mm	85,0 mm
width:	553,0 mm	559,7 mm	540,0 mm
median breadth:			553,0 mm



lids

DET 200

weight: 24,0 g
ISO
volume: 3,00 l

dimensions

Ø lid: 197,0 mm
offset: 145,0 mm
IML: 175,0 mm

stacking height

two fold: 267,0 mm
each
further: 129,0 mm



FDET 200

weight: 28,0 g
ISO
volume: 3,30 l

dimensions

Ø lid: 196,0 mm
offset: 0,0 mm
IML: 0,0 mm

stacking height

two fold: 283,0 mm
each
further: 139,0 mm



DET 200R

weight: 25,0 g
ISO
volume: 3,00 l

dimensions

Ø lid: 197,0 mm
offset: 145,0 mm
IML: 175,0 mm

stacking height

two fold: 269,0 mm
each
further: 131,0 mm



logistic information

Max. compression at 20°C on the lowest pallet: 25,00 kg
layer quantities: 24

Bucket

pieces per pallet: 760

DET 200


pieces per pallet: 4560

FDET 200

pieces per pallet: 4560

DET 200R

pieces per pallet: 4560



material



QM / certificates



general information

In our Technical Guidelines you will find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines "Product" and "Design", which shall also form an integral part of the content of any delivery transaction. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. Technical modifications reserved.