



JET 320

Jokey Euro Tainer Profi



basic data

volume to rim: 34,50 l
weight: 850,0 g
weight group: Medium

handle type: no handle
handle weight: 0.0 g
Side handle

tolerances

dimensions: +/- 1 mm
volume/wieght: +/- 5 %

dimensions

D1: 380,0 mm
D2: 357,8 mm
D3: 320,0 mm
H: 388,0 mm



Remark

decoration


height:
width:
median breadth:

IML

0,0 mm
0,0 mm

Offset

240,0 mm
945,0 mm
1080,0 mm



lids

DET 380

weight: 154,0 g
ISO
volume: 32,90 l

dimensions

Ø lid: 376,0 mm
offset: 270,0 mm
IML: 279,0 mm

stacking height

two fold: 763,0 mm
each
further: 374,0 mm



FDET 380

weight: 178,0 g
ISO
volume: 34,50 l

dimensions

Ø lid: 376,0 mm
offset: 0,0 mm
IML: 0,0 mm

stacking height

two fold: 782,3 mm
each
further: 388,3 mm



DET 380t

weight: 190,0 g
ISO
volume: 32,90 l

dimensions

Ø lid: 376,0 mm
offset: 0,0 mm
IML: 0,0 mm

stacking height

two fold: 763,0 mm
each
further: 374,0 mm



DET 380

weight: 174,0 g
ISO
volume: 32,90 l

dimensions

Ø lid: 376,0 mm
offset: 270,0 mm
IML: 279,0 mm

stacking height

two fold: 763,0 mm
each
further: 374,0 mm



logistic information

Max. compression at 20°C on the lowest pallet: 70,00 kg
layer quantities: 6

Bucket

pieces per pallet: 216

DET 380

pieces per pallet: 1344

FDET 380

pieces per pallet: 1344

DET 380t

pieces per pallet: 900

DET 380

pieces per pallet: 1344



material



QM / certificates



general information

In our Technical Guidelines you will find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport.

Misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines "Product" and "Design", which shall also form an integral part of the content of any delivery transaction. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. Technical modifications reserved.